

Lynx Studio Technology			
name	description	price brutto	
A U R O R A (N)			
Aurora(n) CHASSIS	which is the base model with no modules, no converters, no inputs, etc., then add options	1.349 €	no sold separately
LM-AIO8	<ul style="list-style-type: none"> •8 channels of Aurora(n) line in and out •Hilo Converter Technology (HCT) design and technology borrowed from the Hilo providing Hilo-like quality •Discrete Converter Array with each channel having a self contained shielded circuit for increased dynamic range, lower noise and less crosstalk •Add additional line I/O to an existing 8ch, 16ch or 24ch Aurora(n) •Use for line I/O on Custom Shop Aurora(n) configurations in 8-channel increments 	1180 €	
LM-DIG	<ul style="list-style-type: none"> •16 channels in and 16 channels out of 24-bit AES/EBU, with bit-perfect transmission at sample rates of up to 192kHz •Integrates seamlessly with the mixing and routing engine on the Aurora(n) •Allows the Aurora(n) to replace any current Aurora system that requires AES/EBU connectivity 	429 €	
LM-PRE4	<ul style="list-style-type: none"> •Four-channel microphone/line/HI-Z input module for Aurora(n) •On-board four channel Aurora(n) A/D conversion directly coupled to preamp out •Transformerless, transparent design •Up to 68.6dB gain in 1dB increments •Low noise (-129dBu EIN) microphone input •Independent 48V phantom power, phase, high-pass filter, and pad for each channel •Dedicated line level signal path provides performance identical to LM-AIO8 	749 €	
LT-USB	Up to 16 channels of I/O @ 96 kHz Up to 8 channels of I/O @ 192 kHz	399 €	
LT-HD	One Primary and one Expansion DigiLink port Up to 32 channels per HD Core or Accel Core card Supports full channel count up to 192 kHz only for HILO and silver Aurora 16 & 8	299 €	
LT-HD2	One Primary and one Expansion DigiLink port Up to 32 channels per HD Core or Accel Core card Supports full channel count up to 192 kHz	379 €	
LT-TB	only for HILO and silver Aurora 16 & 8 Two Thunderbolt™ ports Up to 32 channels Supports full channel count up to 192 kHz Can daisy-chain up to Six LT-TB equipped Aurora and Hilo converters,	583 €	
LT-TB3	Two Thunderbolt™ ports Up to 32 channels Supports full channel count up to 192 kHz Can daisy-chain up to Six LT-TB equipped Aurora (n)	679 €	
LT-DANTE	One Primary and one Secondary port Extremely low latency Supports Dante audio networking standard	749 €	

DB-ADAT	DB-ADAT daughter board that brings ADAT and S/PIDF connectivity when paired with an LM-DIG Aurora(n) module	119 €
H I L O		
Hilo USB Silver or Black	Reference A/D D/A Converter System Two-channel 24-bit / 192 kHz Analog I/O Two-channel 24-bit / 192 kHz Digital I/O Headphone Amplifier, Flexible monitor controller LT- USB	2.495 €
Hilo TB3 Silver or Black	Reference A/D D/A Converter System Two-channel 24-bit / 192 kHz Analog I/O Two-channel 24-bit / 192 kHz Digital I/O Headphone Amplifier Flexible monitor controller LT- TB	2.790 €
Hilo Dante Silver or Black	Reference A/D D/A Converter System Two-channel 24-bit / 192 kHz Analog I/O Two-channel 24-bit / 192 kHz Digital I/O Headphone Amplifier, Flexible monitor controller LT- DANTE	2.899 €
Hilo Rack	rack 19' 2 H do zamocowania dówch HILO	130 €
Karty dźwiękowe		
E22	Reference sound card Two-channel 24-bit / 192 kHz Analog I/O Two-channel 24-bit / 192 kHz Digital I/O	839 €
E44	Reference sound card 4-channel 24-bit / 192 kHz Analog I/O 4-channel 24-bit / 192 kHz Digital I/O	1149 €
AES16e	192 kHz Multichannel AES/EBU Interface Thirty-two-channel 24-bit / 192 kHz Digital I/O	849 €
AES16e-SRC	192 kHz Multichannel AES/EBU Interface Thirty-two-channel 24-bit / 192 kHz Digital I/O	959 €
AES16e-50	192 kHz Multichannel AES/EBU Interface Thirty-two-channel 24-bit / 192 kHz Digital I/O AES50 Port Available	1039 €
Akcesoria i kable		
L2/Aur Kit	Allows LynxTWO and Lynx L22 PCI users to add up to16 analog or digital I/O channels. Includes a six-foot cable to connect the LynxTWO or L22 to the included mounting plate, and internal ribbon cable. Adds up to 16 channels of I/O at 48 kHz, 8 channels of I/O at 88.2/96kHz, 4 channels at 176.4/192 kHz.	66 €
AVP-1	Vented Panel	100 €

LS-AES	8-Channel AES/EBU or S/PDIF Interface Module for LynxTWO and Lynx L22 Audio Interfaces	290 €
CBL-AIN85 aurora cable	Analog input cable. Male 25 pin D-sub connector (white shield) to eight female XLR connectors; 5 meters (16.4 feet) long; TASCAM wiring standard.	110 €
CBL-AOUT85 aurora cable	Analog output cable. Male 25 pin D-sub connector (black shield) to eight male XLR connectors; 5 meters (16.4 feet) long; TASCAM wiring standard.	110 €
CBL-DIGY85 aurora cable	Digital input/output cable; eight channels AES/EBU I/O. Male 25 pin D-sub connector (yellow) with four female XLR connectors for input and four male XLR connectors for output; 5 meters (16.4 feet) long; Yamaha pinout configuration.	110 €
CBL-AES1605 aurora cable	26-pin high-density male D-sub to 25-pin male D-sub. Supports 4 stereo (8 mono) channels of input and output. Connects AES16 or AES16e to Aurora digital I/O. Twelve-foot, 110-ohm shielded twisted pair cabling. <i>Note: One cable needed for Aurora 8; pairs are required for Aurora 16.</i>	70 €
CBL-L22Audio	E22 Audio Cable. 2 XLR-M/2 XLR-F to DB25	50 €
CBL-L22Sync	E22 Sync Cable. 2 XLR to HD15 for Digital and 2 BNC for Word Clock I/O	45 €
CBL-L2AudioA	E44 Audio Cable. 4 XLR-M/4 XLR-F to DB25	65 €
CBL-ESYNC	E44 Sync Cable. 4 XLR to HD15 for Digital and 2 BNC for Word Clock I/O	65 €
CBL-XFDR18	S/PDIF Adapter. XLR Female to RCA Male, 18" Long; Digital Out to S/PDIF	20 €
CBL-AES1604 AES16e cable	26-pin high-density male D-sub to four female XLR (8 mono AES input channels), four male XLR (8 mono AES output channels), and one female BNC (word clock I/O). Six-foot, 110-ohm shielded twisted pair cabling.	77 €
LYN-AES16E50 KIT	External CAT5e/6 bracket for AES16e-50.	110 €

Sound import

Am Weingarten 35

90518 Altdorf GERMANY

Mob.: +48 502 671 456; +49 918 790 4377

info@soundimport.pl , www.lynxstudio.eu, www.soundimport.pl